

Polymer Add (Thailand) Co.,Ltd.

Office - 106, Chalarempriakiat, Lor 9, Soi 22, Yak 5, Nongbon, Prawet, Bangkok, Thailand 10250

Factory - 188/3, Moo 8, Tambon Bangpu Mai, Amphoe Muang Samut Prakan, Samutprakan, Thailand 10280

Mobile - Thai : 0804531391, English: 0839415475, E-mail – contact@polymeradd.co.th



SAFETY DATA SHEET (SDS)

Product Name: APPLICOAT MICROBLEND H75

1. Identification of the Substance/Mixture and of the Company/Undertaking

Field	Information
Product Name	APPLICOAT MICROBLEND H75
Relevant Identified Uses	Micronized additive blend for powder coating – appliances (polyester-epoxy systems)
Uses Advised Against	Not intended for pharmaceutical or food use unless tested and certified
Supplier	Polymer Add (Thailand) Co., Ltd
Office Address	106, Chalarempriakiat, Lor 9, Soi 22, Yak 5, Nongbon, Prawet, Bangkok, Thailand 10250
Factory Address	188/3, Moo 8, Bangpu Mai, Muang Samut Prakan, Samutprakan, Thailand 10280
Mobile (Thai)	0804531391
Mobile (English)	0839415475
Email	contact@polymeradd.co.th

2. Hazards Identification

Field	Description
Classification (CLP)	Not classified under Regulation (EC) No. 1272/2008
Classification (67/548/EEC)	Not classified
Label Elements	No hazard pictograms or signal words required
Supplemental	EUH210 - Safety data sheet available on request

3. Composition/Information on Ingredients

Substance	CAS No	Function	% w/w
Micronized PE Wax	9002-88-4	Surface smoothness, gloss, anti-blocking agent	45%
Silica-Coated PE Wax	9002-88-4 / 112945-52-5	Improves powder flow, reduces caking during storage	20%
Synthetic Amide Wax	68953-58-2	Scratch resistance and slip enhancement	10%
Antioxidant 1010	6683-19-8	Thermal stability during extrusion and curing.	3%
Fumed Silica (R972 type)	112945-52-5	Flow aid and anti-caking agent	2%
Slip Additive (Silicone Resin)	63148-62-9	Reduces metal marking and improves fingerprint resistance	5%
Moisture Buffer (optional)	471-34-1 / 112926-00-8	Controls humidity; prevents clumping	15%

Polymer Add (Thailand) Co.,Ltd.

Office - 106, Chalarempriakiat, Lor 9, Soi 22, Yak 5, Nongbon, Prawet, Bangkok, Thailand 10250

Factory - 188/3, Moo 8, Tambon Bangpu Mai, Amphoe Muang Samut Prakan, Samutprakan, Thailand 10280

Mobile - Thai : 0804531391, English: 0839415475, E-mail – contact@polymeradd.co.th



4. First Aid Measures

- **General Advice:** No specific hazards under normal industrial use.
- **Inhalation:** Move to fresh air. Seek medical attention if symptoms persist.
- **Skin Contact:** Wash with soap and water. If irritation occurs, consult a physician.
- **Eye Contact:** Rinse with clean water for several minutes. Seek medical advice if irritation persists.
- **Ingestion:** Rinse mouth. Do not induce vomiting. Seek medical advice if discomfort occurs.

5. Firefighting Measures

- **Extinguishing Media:** Use dry chemical, foam, CO₂, or water spray.
- **Fire Hazards:** May emit CO, CO₂, and hydrocarbons upon thermal decomposition. Fine powder may form explosive dust-air mixtures.
- **Protective Equipment:** Firefighters should wear self-contained breathing apparatus and full protective clothing.

6. Accidental Release Measures

- **Personal Precautions:** Avoid generating dust. Use personal protective equipment (mask, goggles, gloves).
- **Environmental Precautions:** Avoid release to water bodies or drains.
- **Clean-Up Methods:** Sweep or vacuum without raising dust. Collect in suitable containers. Dispose according to local regulations.

7. Handling and Storage

- **Handling:** Avoid inhalation and contact with eyes or skin. Use in well-ventilated areas. Prevent dust formation.
- **Storage:** Store in a cool, dry, well-ventilated area. Keep containers tightly closed and away from moisture and oxidizing agents.

8. Exposure Controls / Personal Protection

Field	Information
OEL (TWA)	No specific limit; follow general dust limits (10 mg/m ³ inhalable, 5 mg/m ³ respirable)
Engineering Controls	Use local exhaust ventilation and dust collection systems
PPE	Dust mask (P2), chemical-resistant gloves, safety goggles
Environmental Controls	Prevent environmental contamination or release to drains

9. Physical and Chemical Properties

Property	Value
Appearance	White to light beige free-flowing powder
Odour	Waxy to neutral

Polymer Add (Thailand) Co.,Ltd.

Office - 106, Chalaremprikat, Lor 9, Soi 22, Yak 5, Nongbon, Prawet, Bangkok, Thailand 10250

Factory - 188/3, Moo 8, Tambon Bangpu Mai, Amphoe Muang Samut Prakan, Samutprakan, Thailand 10280

Mobile - Thai : 0804531391, English: 0839415475, E-mail – contact@polymeradd.co.th



pH (1% dispersion)	Not applicable
Melting Point	95 – 120 °C (blend basis)
Boiling Point	Not applicable
Flash Point	Not applicable
Flammability	Combustible as fine powder
Vapour Pressure	Negligible
Relative Density	0.30 – 0.42 g/cm ³
Solubility in Water	Insoluble
Decomposition Temperature	>200 °C
Explosive Properties	Dust explosion risk under airborne conditions

10. Stability and Reactivity

- **Stability:** Stable under normal conditions of use and storage.
- **Hazardous Reactions:** None known under normal processing.
- **Incompatible Materials:** Strong oxidizing agents and acids.
- **Decomposition Products:** CO, CO₂, hydrocarbons, wax fumes

11. Toxicological Information

Test	Result
Oral LD ₅₀ (rat)	>2000 mg/kg
Skin Irritation	Not irritating under normal use
Eye Irritation	May cause mild mechanical irritation
Sensitization	Not expected
Carcinogenicity	Not listed by IARC, NTP or OSHA

12. Ecological Information

Organism	Test	Result
Fish	LC ₅₀ (96 h, estimated)	>100 mg/L
Daphnia	EC ₅₀ (48 h, estimated)	>100 mg/L
Algae	EC ₅₀ (72 h, estimated)	>100 mg/L

Conclusion:

- Not expected to bioaccumulate.
- Poor water solubility.
- Not readily biodegradable.
- Avoid direct discharge into the environment.

13. Disposal Considerations

- **Product Waste:** Dispose in accordance with applicable local/national regulations.
- **Contaminated Packaging:** Clean thoroughly before reuse or dispose as solid waste.
- **Waste Code (EU):** 07 06 99 – Wastes not otherwise specified

Polymer Add (Thailand) Co.,Ltd.

Office - 106, Chalaremprikat, Lor 9, Soi 22, Yak 5, Nongbon, Prawet, Bangkok, Thailand 10250

Factory - 188/3, Moo 8, Tambon Bangpu Mai, Amphoe Muang Samut Prakan, Samutprakan, Thailand 10280

Mobile - Thai : 0804531391, English: 0839415475, E-mail – contact@polymeradd.co.th



14. Transport Information

Mode	Classification	Remarks
ADR/RID (Road/Rail)	Not regulated	Not classified as dangerous goods
IMDG (Sea)	Not regulated	Not a marine pollutant
ICAO/IATA (Air)	Not regulated	Not restricted
DOT (USA)	Not regulated	Not hazardous for transport

15. Regulatory Information

- **REACH:** Exempt or pre-registered
- **CLP (EC No. 1272/2008):** Not classified
- **Inventories:** All ingredients listed or compliant with TSCA, DSL, AICS, IECSC, ENCS, KECI, PICCS, NZIoC

16. Other Information – APPLICOAT MICROBLEND H75

- **SDS Version:** 1.0 / 2025
- **Date of Preparation:** August 2025
- **Reason for Issue:** First SDS issued for micronized technical blend

Abbreviations:

CAS – Chemical Abstracts Service

CLP – Classification, Labelling and Packaging

REACH – Registration, Evaluation, Authorisation and Restriction of Chemicals

LD₅₀ – Median Lethal Dose

EC₅₀ – Half Maximal Effective Concentration

Disclaimer:

This SDS is provided for industrial handling and transportation purposes only. It does not serve as a product specification or guarantee. Polymer Add (Thailand) Co., Ltd shall not be held liable for misuse or mishandling. Final responsibility lies with the user.